

SDC-EC25N

HARDWARE INTEGRATION GUIDE VERSION 2.1

global solutions: local support ...

Americas: +1-800-492-2320 Option 3

Europe: +44-1628-858-940

Hong Kong: +852-2268-6567 x026

www.lairdtech.com/wireless

SDC-EC25N

Hardware Integration Guide, version 2.1

REVISION HISTORY

Version	Revision Date	Change Description
0.1	05/10/10	Preliminary version of the EC25N HIG.
1.01	06/03/10	Added/revised antenna patterns
2.0	11/08/12	Updated formatting (Laird).
2.1	01/31/13	Updated Channel and Frequency data.

SDC-EC25N

Hardware Integration Guide, version 2.1

CONTENTS

Scope	4
Scope	5
Specifications	5
Pin Definitions	10
Mechanical Specifications	11
Regulatory	12
Documentation Requirements	

SCOPE

This document describes key hardware aspects of the Summit SDC-EC25N wireless LAN radio card. This document is intended to assist device manufacturers and related parties with integration of this card into their host devices. Data in this document are drawn from a number of sources and includes information found in the Broadcom BCM4322 data sheet issued in August of 2008.

OPERATIONAL DESCRIPTION

This device is an SDC-EC25N, an IEEE 802.11n-compliant Peripheral Components Interconnect Express (PCIe) Card which operates in the 2.4 GHz and 5 GH portions of the radio frequency spectrum. The device is compliant with IEEE 802.11a, 802.11b, 802.11g, and 802.11n standards using Direct Sequence Spread Spectrum and Orthogonal Frequency Division Multiplexing. The device supports all 802.11a, 802.11b, and 802.11g data rates and select 802.11n data rates and automatically adjusts data rates and operational modes based on various environmental factors.

When operating on channels in the UNII-2 and UNII-2 Extended bands that are in the 5GHz portion of the frequency spectrum and are subject to Dynamic Frequency Selection requirements, the SDC-EC25N fully conforms to applicable regulatory requirements. In the event that specified types of radar are detected by the network infrastructure, the SDC-EC25N fully conforms with commands from the infrastructure for radar avoidance.



The SDC-EC25N is compliant with 32-bit PCIe Express Card mechanical specifications and interfaces to host devices via a 26-pin connector. The device is based on the Broadcom BCM4322 chip which is an 802.n compliant integrated device providing a Media Access Controller (MAC), a Physical Layer Controller (PHY or baseband processor), and fully integrated dual-band antenna that provides 2x2 antenna and MIMO support. The frequency stability for both 2.4 GHz (802.11b and 802.11g) and 5 GHz (802.11a) operation is +/- 20 ppm.

The SDC-EC25N has its own RF shielding and does not require shielding provided by the host device into which it is installed in order to maintain compliance with applicable regulatory standards. As such, the device may be tested in a standalone configuration via an extender card.


The device buffers all data inputs so that it will comply with all applicable regulations even in the presence of over-modulated input from the host device. Similarly, the SDC-EC25N incorporates power regulation to comply with all applicable regulations even when receiving excess power from the host device.

The SDC-EC25N incorporates an antenna that supports dual band diversity when operating in 802.11a, 802.11b and 802.11g modes and 2×2 MIMO support when operating in 802.11n mode.

The device is labeled with all applicable regulatory information in a manner that's compliant with all regulatory standards. Regulatory operational requirements are included with this document and are to be incorporated into the operating manual of any device into which the SDC-EC25N is installed. The EC25N is designed for installation into mobile devices such as notebook computers which typically operate at distances greater than 20 cm from the human body. See "Documentation Requirements" for more information.

Laird Technologies

BLOCK DIAGRAM



SPECIFICATIONS

Feature	Description
System Interface	32-bit Peripheral Component Interconnect Express (PCIe) Card with 26 pin connector
Antenna	Dual Band for diversity and 2 x 2 MIMO support
Chip Set	Broadcom BCM4322
Input Power Requirements	3.3 VDC +/- 10%
Current Consumption (At maximum transmit power setting)	Transmit: 600 mA (1980 mW) Receive: 450 mA (1485 mW) Standby: TBD mA (TBD mW)
Operating Temperature	-30° to 75°C (-22° to 167°F)
Operating Humidity	10 to 90% (non-condensing)
Storage Temperature	-40° to 80°C (-40° to 176°F)

Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940

Feature	Description
Storage Humidity	10 to 90% (non-condensing)
Maximum Electrostatic Discharge	4 kV
Length	99.35 mm (3.91 in.)
Width	33.57 mm (1.32 in.)
Thickness	4.75 mm 0.18 in.)
Weight	15 g (0.53 oz.)
Mounting	26-pin connector and standard Express Card rails
Wireless Media	Direct Sequence-Spread Spectrum (DSSS) Orthogonal Frequency Divisional Multiplexing (OFDM)
Media Access Protocol	Carrier sense multiple access with collision avoidance (CSMA/CA)
Network Architecture Types	Infrastructure and ad hoc
Network Standards	IEEE 802.11a, 802.11b, 802.11d, 802.11e, 802.11g, 802.11h, 802.11i, 802.11n
Data Rates Supported	802.11a (OFDM): 6, 9, 12, 18, 24, 36, 48, 54 802.11b (DSSS): 1, 2, 5.5, 11 802.11g (OFDM): 6, 9, 12, 18, 24, 36, 48, 54 802.11n (OFDM, 20-MHz channels): 14, 29, 43, 58, 87, 116, 130, 144 802.11n (OFDM 40-MHz channels): 30, 60, 90, 120, 180, 240, 270, 300
Modulation	BPSK @ 1, 6, 9, 14, 30 Mbps QPSK @ 2, 12, 18, 29, 43, 60, 90 Mbps CCK @ 5.5,11 Mbps 16-QAM @ 24, 36, 58, 87, 120, 180 Mbps 64-QAM @ 48, 54, 116, 130, 144, 240, 270, 300 Mbps
Modulation and Coding Scheme (MCS) Index Values Supported	0–15
Regulatory Domain Support	FCC (Americas, Parts of Asia and Middle East) ETSI (Europe, Middle East, Africa and Parts of Asia) MIC (formerly TELEC) (Japan) KCC (Korea)
2.4 GHz Frequency Bands	ETSI 2.4 GHz to 2.483 GHz FCC 2.4 GHz to 2.473 GHz

Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940 Hong Kong: +852-2268-6567 x026 www.lairdtech.com/wireless

Feature	Description
	MIC (formerly TELEC) 2.4 GHz to 2.495 GHz KCC 2.4 GHz to 2.483 GHz
5 GHz Frequency Bands	ETSI 5.15 GHz to 5.35 GHz 5.47 GHz to 5.725 GHz FCC 5.15 GHz to 5.35 GHz 5.47 GHz to 5.725 GHz 5.725 GHz to 5.82 GHz MIC (formerly TELEC) 5.15 GHz to 5.35 GHz
	KCC 5.15 GHz to 5.35 GHz 5.725 GHz to 5.82 GHz
2.4 GHz, 20 MHz-wide Operating Channels	ETSI: 13 (3 non-overlapping) FCC: 11 (3 non-overlapping) MIC: 14 (4 non-overlapping) KCC: 13 (3 non-overlapping)
5 GHz, 20 MHz-wide Operating Channels	ETSI: 19 non-overlapping FCC: 23 non-overlapping MIC: 8 non-overlapping KCC: 12 non-overlapping
5 GHz, 40 MHz-wide Operating Channels	ETSI: 9 non-overlapping FCC: 11 non-overlapping MIC: 4 non-overlapping
Transmit Power Settings	802.11a: 14 dBm (25 mW) 802.11b:
Note: Maximum transmit power varies according to individual country regulations. All values nominal, +/-2 dBm	17 dBm (50 mW) 802.11g: 17 dBm (50 mW) 802.11n (20 MHz wide 2.4 GHz channel operation): 17 dBm (50 mW) 802.11n (40 MHz wide 2.4 GHz channel operation): 14 dBm (25 mW) 802.11n (20 MHz wide 5 GHz channel operation): 15 dBm (30 mW) 802.11n (40 MHz wide 5 GHz channel operation): 14 dBm (25 mW)

Feature	Description	
Typical Receiver Sensitivity	802.11a	
Typical Neceiver Sensitivity	6 Mbps	-85 dBm
	12 Mbps	-83 dBm
Note: We cannot currently test Typical	18 Mbps	-80 dBm
Receiver Sensitivity for 802.11n due	24 Mbps	-76 dBm
to lack of availability of an applicable	36 Mbps	-73 dBm
AP (one that functions in Greenfield	48 Mbps	-70 dBm
mode). We will have these numbers	54 Mbps	-65 dBm (PER <= 10%)
as soon as possible.	802.11b	
	1 Mbps	-96 dBm
	2 Mbps	-95 dBm
	5.5 Mbps	-94 dBm
	11 Mbps	-90 dBm (PER <= 10%)
	802.11g	<u> </u>
	6 Mbps	-94 dBm
	12 Mbps	-88 dBm
	18 Mbps	-86 dBm
	24 Mbps	-83 dBm
	36 Mbps	-78 dBm
	48 Mbps	-76 dBm
	54 Mbps	-75 dBm (PER <= 10%)
) MHz channels)
	13 Mbps	TBD dBm
	26 Mbps	TBD dBm
	39 Mbps	TBD dBm
	52 Mbps	TBD dBm
	78 Mbps	TBD dBm
	104 Mbps	TBD dBm
	117 Mbps	TBD dBm
	130 Mbps	TBD dBm (PER <= 10%)
) MHz channels)
	27 Mbps	TBD dBm
	54 Mbps	TBD dBm
	81 Mbps	TBD dBm
	108 Mbps	TBD dBm
	162 Mbps	TBD dBm
	216 Mbps	TBD dBm
	243 Mbps	TBD dBm
	270 Mbps	TBD dBm (PER <= 10%)
	_, c 1110ps	32 (. 2 1 70)

Feature	Description	
Delay Spread	600 ns @ 1 Mbps 500 ns @ 2 Mbps 400 ns @ 5.5 Mbps 400 ns @ 6 Mbps 400 ns @ 9 Mbps 200 ns @ 11 Mbps 350 ns @ 12 Mbps 350 ns @ 18 Mbps 250 ns @ 24 Mbps 250 ns @ 36 Mbps 150 ns @ 48 Mbps 150 ns @ 48 Mbps	
Security	Standards Wireless Equivalent Privacy (WEP) Wi-Fi Protected Access (WPA) IEEE 802.11i (WPA2) Encryption Wireless Equivalent Privacy (WEP, RC4 Algorithm) Temporal Key Integrity Protocol (TKIP, RC4 Algorithm) Advanced Encryption Standard (AES, Rijndael Algorithm) Encryption Key Provisioning Static (40-bit and 128-bit lengths) Pre-Shared (PSK) Dynamic 802.1X Extensible Authentication Protocol Types EAP-FAST PEAP-GTC EAP-TLS PEAP-MSCHAPv2 EAP-TLS PEAP-TLS	
Operating Systems Supported	Windows XP Professional and Embedded	
Compliance	ETSI Regulatory Domain EN 300 328 EN 301 489-1 EN 301 489-17 EN 301 893 EN 60950-1 EU 2011/65/EU (RoHS) FCC Regulatory Domain Part 15.247 Subpart C Part 15.407 Subpart E	

Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940

Feature	Description
	Industry Canada
	RSS-210
	RSS-Gen Issue 2
	MIC Regulatory Domain
	Article 2 Item 19, Category WW (2.4GHz Channels 1-13)
	Article 2 Item 19-2, Category GZ (2.4GHz Channel 14)
	Article 2 Item 19-3 Category XW (5150-5250 W52 & 5250-5350
	<u>W53)</u>
Certifications	Wi-Fi Alliance
Certifications	802.11a, 802.11b, 802.11g, 802.11n Wi (Fi)
	WPA Enterprise CERTIFIED
	WPA2 Enterprise
	Cisco Compatible Extensions
Warranty	Limited Lifetime

All specifications are subject to change without notice

PIN DEFINITIONS

Note: The following are industry-standard express card pinouts for reference only.


Pin Number	Pin Name	I/O	Power Supply	Description	Note	
1	GND	GND		Ground		
2	No Connect			Not Used. Leave Open (Float)		
3	No Connect			Not Used. Leave Open (Float)		
4	No Connect			Not Used. Leave Open (Float)		
5	No Connect			Not Used. Leave Open (Float)		
6	No Connect			Not Used. Leave Open (Float)		
7	No Connect			Not Used. Leave Open (Float)		
8	No Connect			Not Used. Leave Open (Float)		
9	VCC1_5			Primary 1.5 V Module Power		
10	VCC1_5			Primary 1.5 V Module Power		
11	WL_GPIO_1			Wake on Wireless LAN		
12	VAUX_3_3			Auxiliary 3.3 V Module Power		
13	PERST_L			Module Reset		
14	VCC3_3			Primary 3.3 V Module Power		
15	VCC3_3			Primary 3.3 V Module Power		
16	CLKREQ_L			Reference clock request signal		

Americas: +1-800-492-2320 Option 3

Europe: +44-1628-858-940 Hong Kong: +852-2268-6567 x026 www.lairdtech.com/wireless

Pin Number	Pin Name	1/0	Power Supply	Description	Note
17	No Connect			Not Used. Leave Open (Float)	
18	REFCLK_N			Differential reference clock	
19	REFCLK_P			Differential reference clock	
20	GND			Ground	
21	PERn0			Differential transmit	
22	PERp0			Differential transmit	
23	GND			Ground	
24	PETn0			Differential receive	
25	PETp0			Differential receive	
26	GND			Ground	

MECHANICAL SPECIFICATIONS



The SDC-EC25N is fully compliant with the PCI Express Card Type 1 mechanical standard. It can therefore be inserted in any Express Card hardware interface and typically does not require any additional mounting hardware.

11

REGULATORY

Note: Operation in the 5150-5250 MHz band is limited to indoor use only in some regulatory domains.


Antenna Characteristics

The SDC-EC25N incorporates an integrated dual band antenna consisting of two separate antenna elements to support transmit and receive diversity and 2 x 2 MIMO. The patterns for two separate antenna elements are below:

Type: Dipole


Maximum 2.4 GHz Gain: 0 dBi Maximum 5 GHz Gain: 0 dBi

Antenna 1 Patterns



Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940

Antenna 2 Patterns



Documentation Requirements

In order to maintain regulatory compliance, when integrating the SDC-EC25N into a host device and leveraging Summit's grants and certifications, it is necessary to meet the documentation requirements set forth by the applicable regulatory agencies. The following sections (FCC, Industry Canada, and European Union) outline the information that may be included in the user's guide and external labels for the host devices into which the SDC-EC25N is integrated.

SDC-EC25N approvals are based on the SDC-PE15N.

FCC

User's Guide Requirements

As outlined in the Operational Description, the SDC-EC25N complies with <u>FCC Part 15 Rules</u> for a Modular Approval. To leverage Summit's grant, the two conditions below must be met for the host device into which the SDC-EC25N is integrated:

13

Hardware Integration Guide, version 2.1

- 1. The antenna is installed with 20 cm maintained between the antenna and users.
- 2. The transmitter module is not co-located with any other transmitter or antenna that is capable of simultaneous operation.

As long as the two conditions above are met, further *transmitter* testing is typically not required. However, the OEM integrator is still responsible for testing its end-product for any additional compliance requirements required with this module installed, such as (but not limited to) digital device emissions and PC peripheral requirements.

IMPORTANT!

In the event that the two conditions above *cannot be met* (for example certain device configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID *cannot* be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

When using Summit's FCC grant for the SDC-EC25N, the integrator must include specific information in the user's guide for the device into which the SDC-EC25N is integrated. The integrator must not provide information to the end user regarding how to install or remove this RF module in the user's manual of the device into which the SDC-EC25N is integrated. The following FCC statements must be added in their entirety and without modification into a prominent place in the user's guide for the device into which the SDC-EC25N is integrated:

"IMPORTANT NOTE: To comply with FCC RF exposure compliance requirements, the antenna used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter."

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- 1. Reorient or relocate the receiving antenna.
- 2. Increase the separation between the equipment and receiver.
- 3. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- 4. Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940

IMPORTANT NOTE: FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Industry Canada

User's Guide Requirements

As outlined in the Operational Description, the SDC-EC25N complies with Industry Canada (IC) rules for a Limited Modular Approval. To leverage Summit's grant, the two conditions below must be met for the host device into which the SDC-EC25N is integrated:

- 1. The antenna is installed with 20 cm maintained between the antenna and users.
- 2. The transmitter module is not co-located with any other transmitter or antenna that is capable of simultaneous operation.

As long as the two conditions above are met, further *transmitter* testing is typically not required. However, the OEM integrator is still responsible for testing its end-product for any additional compliance requirements required with this module installed, such as (but not limited to) digital device emissions and PC peripheral requirements.

IMPORTANT!

In the event that the two conditions above *cannot be met* (for example certain device configurations or co-location with another transmitter), then the IC authorization is no longer considered valid and the IC ID *cannot* be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate IC authorization.

When using Summit's IC grant for the SDC-EC25N, the integrator must include specific information in the user's guide for the device into which the SDC-EC25N is integrated. The integrator must not provide information to the end user regarding how to install or remove this RF module in the user's manual of the device into which the SDC-EC25N is integrated. In addition to the required FCC statements outlined above, the following IC statements must be added in their entirety and without modification into a prominent place in the user's guide for the device into which the SDC-EC25N is integrated:

To prevent radio interference to the licensed service, this device is intended to be operated indoors and away from windows to provide maximum shielding. Equipment (or its transmit antenna) that is installed outdoors is subject to licensing.

European Union

User's Guide Requirements

The integrator must include specific information in the user's guide for the device into which the SDC-EC25N is integrated. In addition to the required FCC and IC statements outlined above, the following R&TTE statements must be added in their entirety and without modification into a prominent place in the user's guide for the device into which the SDC-EC25N is integrated:

This device complies with the essential requirements of the R&TTE Directive 1999/5/EC. The following test methods have been applied in order to prove presumption of conformity with the essential requirements of the R&TTE Directive 1999/5/EC:

EN60950-1:2001 A11:2004

Americas: +1-800-492-2320 Option 3 Europe: +44-1628-858-940

Hardware Integration Guide, version 2.1

Safety of Information Technology Equipment

EN 300 328 V1.7.1: (2006-10)

Electromagnetic compatibility and Radio spectrum Matters (ERM); Wideband Transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using spread spectrum modulation techniques; Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive

EN 301 489-1 V1.6.1: (2005-09)

Electromagnetic compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements

EN 301 489-17 V1.2.1 (2002-08)

Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for 2,4 GHz wideband transmission systems and 5 GHz high performance RLAN equipment

EN 301 893 V1.5.1 (2008-12)

Electromagnetic compatibility and Radio spectrum Matters (ERM); Broadband Radio Access Networks (BRAN); Specific conditions for 5 GHz high performance RLAN equipment

EU 2002/95/EC (RoHS)

Declaration of Compliance – EU Directive 2003/95/EC; Reduction of Hazardous Substances (RoHS)

This device is a 2.4 GHz wideband transmission system (transceiver), intended for use in all EU member states and EFTA countries, except in France and Italy where restrictive use applies.

In Italy the end-user should apply for a license at the national spectrum authorities in order to obtain authorization to use the device for setting up outdoor radio links and/or for supplying public access to telecommunications and/or network services.

This device may not be used for setting up outdoor radio links in France and in some areas the RF output power may be limited to 10 mW EIRP in the frequency range of 2454 – 2483.5 MHz. For detailed information the end-user should contact the national spectrum authority in France.

් Česky [Czech]	[Jméno výrobce] tímto prohlašuje, že tento [typ zařízení] je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 1999/5/ES.
da Dansk [Danish]	Undertegnede [fabrikantens navn] erklærer herved, at følgende udstyr [udstyrets typebetegnelse] overholder de væsentlige krav og øvrige relevante krav i direktiv 1999/5/EF.
de Deutsch [German]	Hiermit erklärt [Name des Herstellers], dass sich das Gerät [Gerätetyp] in Übereinstimmung mit den grundlegenden Anforderungen und den übrigen einschlägigen Bestimmungen der Richtlinie 1999/5/EG befindet.
et Eesti [Estonian]	Käesolevaga kinnitab [tootja nimi = name of manufacturer] seadme [seadme tüüp = type of equipment] vastavust direktiivi 1999/5/EÜ põhinõuetele ja nimetatud direktiivist tulenevatele teistele asjakohastele sätetele.
en English	Hereby, [name of manufacturer], declares that this [type of equipment] is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.
Español [Spanish]	Por medio de la presente [nombre del fabricante] declara que el [clase de equipo] cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o

Americas: +1-800-492-2320 Option 3

Europe: +44-1628-858-940 Hong Kong: +852-2268-6567 x026 www.lairdtech.com/wireless

	exigibles de la Directiva 1999/5/CE.			
el Ελληνική [Greek]	ΜΕ ΤΗΝ ΠΑΡΟΥΣΑ [name of manufacturer] ΔΗΛΩΝΕΙ ΟΤΙ [type of equipment] ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 1999/5/ΕΚ.			
fr Français [French]	Par la présente [nom du fabricant] déclare que l'appareil [type d'appareil] est conforme aux exigences essentielles et aux autres dispositions pertinentes de la directive 1999/5/CE.			
it Italiano [Italian]	Con la presente [nome del costruttore] dichiara che questo [tipo di apparecchio] è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 1999/5/CE.			
Latviski [Latvian]	Ar šo [name of manufacturer / izgatavotāja nosaukums] deklarē, ka [type of equipment / iekārtas tips] atbilst Direktīvas 1999/5/EK būtiskajām prasībām un citiem ar to saistītajiem noteikumiem.			
Lietuvių [Lithuanian]	Šiuo [manufacturer name] deklaruoja, kad šis [equipment type] atitinka esminius reikalavimus ir kitas 1999/5/EB Direktyvos nuostatas.			
ા Nederlands [Dutch]	Hierbij verklaart [naam van de fabrikant] dat het toestel [type van toestel] in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 1999/5/EG.			
Mt Malti [Maltese]	Hawnhekk, [isem tal-manifattur], jiddikjara li dan [il-mudel tal-prodott] jikkonforma mal-ħtigijiet essenzjali u ma provvedimenti oħrajn relevanti li hemm fid-Dirrettiva 1999/5/EC.			
hu Magyar [Hungarian]	Alulírott, [gyártó neve] nyilatkozom, hogy a [típus] megfelel a vonatkozó alapvető követelményeknek és az 1999/5/EC irányelv egyéb előírásainak.			
Polski [Polish]	Niniejszym [nazwa producenta] oświadcza, że [nazwa wyrobu] jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 1999/5/EC.			
Português [Portuguese]	[Nome do fabricante] declara que este [tipo de equipamento] está conforme com os requisitos essenciais e outras disposições da Directiva 1999/5/CE.			
Slovensko [Slovenian]	[Ime proizvajalca] izjavlja, da je ta [tip opreme] v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 1999/5/ES.			
Slovensky [Slovak]	[Meno výrobcu] týmto vyhlasuje, že [typ zariadenia] spĺňa základné požiadavky a všetky príslušné ustanovenia Smernice 1999/5/ES.			
fi Suomi [Finnish]	[Valmistaja = manufacturer] vakuuttaa täten että [type of equipment = laitteen tyyppimerkintä] tyyppinen laite on direktiivin 1999/5/EY oleellisten vaatimusten ja sitä koskevien direktiivin muiden ehtojen mukainen.			
Svenska [Swedish]	Härmed intygar [företag] att denna [utrustningstyp] står I överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 1999/5/EG.			