Laird TECHNOLOGIES®

Innovative **Technology** for a **Connected** World

Flat Panel Antenna
PA35-13

3400 TO 3600 MHz OPERATION FLAT PANEL ANTENNA

The 3.5 GHz Flat Panel Directional antennas by Laird Technologies offer high gain in a thin low profile package. The antennas are constructed of a gray color UV Resistant ABS plastic radome with an aluminum backplate. The antenna can be used in Horizontal or Vertical Polarization. The die cast aluminum bracket affords ±45° up or down tilt adjustment and the stainless steel hardware assures a long service life. The antenna can be surface mounted or pole mounted. The antenna comes with an integral N female connector standard.

FEATURES ✓RoHS

- High gain/low profile
- Pole mount or surface mount
- Rugged and weatherproof
- Vertical or horizontal polarization
- Type N female connector

MARKETS

- 3.5 GHz wireless LAN applications
- Client antennas
- WiMAX

ANTENNA PATTERNS



global solutions: local support™

Americas: +1.847 839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

Laird TECHNOLOGIES®

Innovative **Technology** for a **Connected** World

Flat Panel Antenna
PA35-13

SPECIFICATIONS

PARAMETER	MIN	TYP	MAX	UNITS
Frequency Range	3400		3600	MHz
Gain		13		dBi
Horizontal Beamwidth		35		Deg
Vertical Beamwidth		35		Deg
Front to Back	20			dB
Cross Polarization	20			dB
VSWR		1.5:1		
Impedance		50		OHM
Input Power			100	W
Operating Temperature	-40		+70	°C
Pole Size	1 (25)		2.5 (64)	in (mm)
Weight		17.6 (0.5)		oz (kg)
Dimension (L x W x Thick)		7.5 x 7.5 x 0.8 (190 x 190 x 20)		in (mm)
Bracket Tilt		45		Deg

WIND LOADING (LBS.)

MODEL	SQ. IN	100 MPH	125 MPH	100 MPH WITH ½ IN RADIAL ICE
PA35-13	56	14 lbs	22 lbs	14 lbs

SYSTEM ORDERING INFORMATION

PA35-13 3.4 to 3.6 GHz 13 dBi Flat Panel Directional Antenna

NOTES

- All shipments F.O.B. Schaumburg, IL 60173

ANT-DS-PA35-13 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.